



ADD-ON CAMERA

SVA040-D

Driver Facing Camera



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- 1/3" Next Chip NEPIS CCD, Sony
- Wide View 145°, (2.45mm)Lens
- 650 TV lines
- Wide Dynamic Range (WDR)
- Digital Noise Reduction (DNR)
- DC 5~12V 12
- Infrared LEDs for Night-time Recording
- Easy Windshield Installation with 3M Adhesive
- Simple and Secure Angle Control

SVA040-D Technical Specifications



Resolution		Horizontal: 650 TV Lines	
Synchronization		Internal	
White Balance		2000 ~ 8000K Automatic Tracking	
D-WDR		Off / Low / Middle / High	
Power Supply		DC 5V~12V: 290 mA (LED ON)	
Day and Night	True Day / Night	Night View Distance	7M
Storage Temperature	-30°C ~ +80°C	Operating Temperature	-20°C ~ +60°C
Dimensions		80.5mm (W) x 50.5mm (D) x 61.0mm (H)	
Language		English	
Housing Color		Black	
Mirror		ON/ OFF (Option)	
Image Device		1/3" Next Chip NEPIS CCD Sony	
Image Processor		NEXT CHIP Image Signal Processor NVP 2080	
AGC		Off / Low / Middle / High	
Effective Pixels		(H)768 x (V) 494(NTSC) / (H) 752 x (V)582 (PAL)	
Video Output		CVBS 1Vp-p ± 10%, 75 Ω	
Scanning Mode		2:1 interlace	
BLC		Off / Low / Middle / High	
Scan Frequency		(V)59.94 Hz, (H)15.734 KHz (NTSC)(V)50 Hz, (H) 15.625 KHz (PAL)	
Infrared LED		12 Infrared LEDs	
Lens		2.45mm lens (145°)	
Sensitivity		01 Lux (F1.2, @ 50 IRE)	
S/N Ratio		More than 50dB AGC OFF	
Compatible Hardware Platforms		CP4S, CRXS	
Required Accessories		CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A	
Warranty		2-year standard	