



HARDWARE PLATFORM

# CP4S

4 Channel HD  
Vehicle Recorder



## VISIBILITY + PROTECTION

The CP4S is an HD, cloud-connected mini-DVR designed to record high-resolution telematics data providing powerful insights into driving dynamics like harsh braking, cornering and accelerating. Supporting up to 4 cameras, video can be captured in and around vehicles with an optional monitor to increase driver visibility. Events, including accidents, are automatically uploaded to the cloud along with live-stream and historical data access available. Packed with sensors and high-speed connectivity, the CP4S provides real-time decision making capabilities for operators and managers to coach drivers, capture incidents and reduce cost.

## HIGHLIGHTS

### Gain Control

Take telematics to the next level with video that transforms ordinary data into insight.

### Mitigate Risk

Eliminate the unexpected with a solution to improve driver performance and get ahead of dangerous behavior.

### Protect Your Future

Invest in solutions that will fit your needs today and expand with your growing business.

+

- 1080p HD video with up to 4 camera inputs
- Multiple camera options with plug-and play compatibility
- Supports 128GB storage capacity
- 4G/LTE data transmission for instant notification of events
- Compact and secure design

# CP4S Technical Specifications



<b>Size / Weight</b>	120 mm x 28mm x 90 mm / 166 g
<b>LED</b>	Green LED (network), Blue LED (recording), Red LED (error)
<b>RTC</b>	Internal battery
<b>Operational Temperature</b>	-10° C ~ 55° C
<b>Super Capacitor</b>	Enables recording of last file & safe shutdown
<b>Power Consumption</b>	Max. 36 W
<b>Recording Resolution</b>	Up to 4 Channels HD
<b>Recording Speed</b>	4 Channels HD at 15 FPS
<b>Recording Mode</b>	Continuous, Event and Dual Mode
<b>AV In/Out</b>	1 x Audio in (internal/external microphone) / 1 x Video out; 1 x Audio out
<b>Storage</b>	Supports SD Cards Up to 256 GB
<b>Cellular</b>	CP4S-NA: [CAT4] B2/B4/B5/B12/B13/B14/B66/B71; [3G] B2/B4/B5 CP4S-EU: [CAT4] B1/B3/B7/B8/B20/B28A/B38/B40/B41; [3G] B1/B8
<b>Delayed Power Shutdown</b>	Yes
<b>GPS / GLONASS</b>	External GPS / GLONASS
<b>G-Sensor</b>	Internal 3-axis G-sensor
<b>Gyro</b>	3 Axis (X,Y,Z), Output Rate: 100 Hz
<b>Alarm In / Out</b>	4 x Alarm in / 1 x Alarm out
<b>Max Data Rate</b>	Download: 100 Mbps; Upload: 50 Mbps
<b>WiFi</b>	Built In with CP4S-W Mode
<b>Power Input</b>	DC 12V/24V, 3A
<b>SmartAPI Integrated</b>	Yes
<b>Data Analysis Software</b>	Windows only
<b>Viewer Software</b>	Windows and MacOS
<b>Warranty</b>	2-year standard