



ADD-ON CAMERA

# SVA034-AWP

Mini Dome Camera



## HIGHLIGHTS

### Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

### High Quality

Built with premium components to ensure excellent picture quality in any conditions.

### Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- Three Mounting Options ( 0°, 15°, 25° )
- Sony 1/3.2"
- 2.8mm Lens
- 720P AHD
- Diagonal Field of View 105°
- Digital Noise Reduction (DNR)
- DC 12V
- Infrared LEDs for Night-time Recording
- Simple and Secure Angle Control

# SVA034-AWP Technical Specifications



<b>Synchronization</b>	Internal	<b>TV Mode</b>	PAL
<b>Electronic Shutter</b>		Auto	
<b>Infrared Spectrum</b>		850nm	
<b>Power Supply</b>		12V DC±10%	
<b>Audio</b>	Available	<b>Power Consumption</b>	170mA (Max)
<b>ICR</b>	Available	<b>Operating Temperature</b>	-30° C ~ +70 ° C
<b>Dimensions (ø X H)</b>		77 x 60.3 mm	
<b>Net Weight</b>		200 g	
<b>Weatherproof/ Water Proof</b>	IP66	<b>Mirror</b>	OFF
<b>Image Sensor</b>		Sony 1/3.2"	
<b>Noise Reduction</b>		3D	
<b>AGC</b>		Auto	
<b>Picture Elements</b>		1280 (H) x 960 (V)	
<b>Video Output</b>		1 Vp-p, 75Ω,AHD	
<b>Scanning System</b>		Progressive scan RGB CMOS	
<b>BLC</b>		Auto	
<b>Dynamic range</b>		120 dB	
<b>Infrared LED</b>		10 LEDs (ø3.0)	
<b>Lens</b>		F2.8mm Megapixel	
<b>Sensitivity</b>		0 Lux (IR LED On)	
<b>S/N Ratio</b>		More than 44dB (AGC Off)	
<b>Compatible Hardware Platforms</b>		CP4S, CRXS	
<b>Required Accessories</b>		CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A	
<b>Warranty</b>		2-year standard	