



ADD-ON CAMERA

SVA034-A

Mini Dome Camera



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- Three Mounting Options (0°, 15°, 25°)
- 1/3" CMOS AR0130
- 2.8mm Lens
- 720P AHD
- Diagonal Field of View 105°
- Digital Noise Reduction (DNR)
- DC 5~12V 12
- Infrared LEDs for Night-time Recording
- Simple and Secure Angle Control

SVA034-A Technical Specifications



Synchronization	Internal	TV Mode	NTSC
Electronic Shutter		Auto	
Infrared Spectrum		850nm	
Power Supply		9-18V DC	
Audio	Available	Power Consumption	145mA(Max)
ICR	Available	Operating Temperature	-30° C ~ +70 ° C
Dimensions (ø X H)		77 x 60.3 mm	
Net Weight		200 g	
Weatherproof/ Water Proof	IP66	Mirror	OFF
Image Sensor		1/3" CMOS AR0130	
Noise Reduction		3D	
AGC		Auto	
Effective Pixels		1280 (H) x 960 (V)	
Video Output		1 Vp-p, 75Ω,AHD (CVBS)	
Scanning Mode		Progressive scan RGB CMOS	
BLC		Auto	
Dynamic range		83.5 dB	
Infrared LED		10 LEDs (ø3.0)	
Lens		F2.8mm Megapixel	
Sensitivity		0 Lux (IR LED On)	
S/N Ratio		More than 44dB (AGC Off)	
Compatible Hardware Platforms		CP4S, CRXS	
Required Accessories		CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A	
Warranty		2-year standard	